

4BZ6

Semiremote-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BZ6 is the same as the 6BZ6 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater current = 0.450	4.2	volts
Warm-up time (Average).	11	sec

4BZ7

Medium-Mu Twin Triode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BZ7 is the same as the 6BZ7 except for the following items:

Heater Characteristics and Ratings (*Design-Center Values*):

Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater current = 0.600	4.2	volts
Warm-up time (Average).	11	sec

4CB6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4CB6 is the same as the 6CB6 except for the following items:

Heater Characteristics and Ratings (*Design-Center Values*):

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater current = 0.450	4.2	volts
Warm-up time (Average).	11	sec
Peak heater-cathode voltage:		
Heater negative with respect to cathode.	300 ^a max.	volts
Heater positive with respect to cathode.	200 ^b max.	volts

^a The dc component must not exceed 200 volts.

^b The dc component must not exceed 100 volts.

RADIO CORPORATION OF AMERICA
Electron Tube Division

Harrison, N. J.

